

..

## TP SERIES 350-450-G Commercial Washer-Extractor

FWH-100 LBS FWH-135 LBS FWH-275 LBS



The latest features and technology at you service:



1







Powerful Flexible "Control your budget"

The laundry operator can easily program, retrieve data and create wash cycle reports through USB and laptop PC. A simple access to data bank and easy programming the TP control helps save time and ensures the correct laundry process. Trouble shooting friendly.

Built to Last Ergonomic Door System

Loading and unloading are fast and easy through the oversized ergonomic door system that opens 180 degrees. No more wasted time due to door lock error codes. Fagor maintained your laundry business

running at a full productivity.

## User friendly Tilting System

The optimized & friendly tilting system make your laundry operation more efficient, assist the operator in the loading & unloading process & increasing production .

## Quality Construction and Durability

Rugged frame design offers excellent strength and stability for better performance. Washer feature inner, outer cylinder, front and side panels of durable stainless steel. Oversize bearings and housing assure superior quality & longevity over the life time of the washer.



High Speed Industrial-Commercial Strength Washer-Extractor, a Fagor Commercial product line, engineered to deliver energy efficiency, performance and to manage unmatched wash quality performance. The robust design will last for years and the performance has proven to be extremely reliable in the industry.

MODELS	FWH-100TP	FWH-135TP	FWH-275TP
LOAD CAPACITY (lb/kg)	100 / 45	135/60	275/120
CYLINDER VOLUME (cu. ft. / liter)	15.89 / 450	21.19/600	42.38 / 1200
CYLINDER DIAMETER (in / mm)	36.14/918	41.26 / 1048	53.54 / 1360
CYLINDER DEPTH (in / mm)	28.35 / 720	26.93 / 684	33.07 / 840
WIDTH (in / mm)	58.19/1478	58.19/1478	72.28 / 1836
DEPTH (cabinet) (in / mm)	56.85 / 1444	31-1/2 / 1444	73.35 / 1863
DEPTH (overall) (in / mm)	/	/	/
HEIGHT (in / mm)	75 / 1905	75 / 1905	88.39 / 2245
WEIGHT (Ib/kg)	2976.24 / 1350	3086 / 1400	8708.25 / 3950
SHIPPING DIMENSIONS APPROX - in (in / mm)	with packaging		
CRATED WIDTH (in / mm)	60.63 / 1540	60.63 / 1540	74.80 / 1900
CRATED DEPTH (in / mm)	62.20 / 1580	62.20 / 1580	76.38 / 1940
CRATED HEIGHT (in / mm)	77.56 / 1970	77.56 / 1970	90.16 / 2290
CRATED WEIGHT (Ib / kg)	3130.56 / 1420	3351 / 1520	9038.94 / 4100
DOOR			
HEIGHT TO BOTTOM OF DOOR in mm	46 / 30.67 1190 / 830	46 / 30.67 1190 / 830	52.36 / 35.43 1330 / 900
		11007 000	
DOOR OPENING DIAMETER (in / mm)	22.05 / 560	22.05 / 560	27.56 / 700
		22.05 / 560	
DOOR OPENING DIAMETER (in / mm)		22.05 / 560 208-240 / 3PH	
DOOR OPENING DIAMETER (in / mm)	22.05 / 560		27.56 / 700
DOOR OPENING DIAMETER (in / mm) POWER VOLTAŒ / Phase (50 hz or 60 hz)	22.05 / 560 208-240 / 3PH	208-240 / 3PH	27.56 / 700 208-240 / 3PH
DOOR OPENING DIAMETER (in / mm) POWER VOLTAŒ / Phase (50 hz or 60 hz) Full Load Ourrent / Breaker (amps) - 1PH	22.05 / 560 208-240 / 3PH	208-240 / 3PH	27.56 / 700 208-240 / 3PH
DOOR OPENING DIAMETER (in / mm) POWER VOLTACE / Phase (50 hz or 60 hz) Full Load Ourrent / Breaker (amps) - 1PH CONNECTIONS	22.05 / 560 208-240 / 3PH 7.5 / 25	208-240 / 3PH 11 / 40	27.56 / 700 208-240 / 3PH 15 / 50
DOOR OPENING DIAMETER (in / mm) POWER VOLTACE / Phase (50 hz or 60 hz) Full Load Ourrent / Breaker (amps) - 1PH CONNECTIONS Water Inlet (GHT / BSP)	22.05 / 560 208-240 / 3PH 7.5 / 25 1" / 1"	208-240 / 3PH 11 / 40 1" / 1"	27.56 / 700 208-240 / 3PH 15 / 50 1.5" / 1.5"
DOOR OPENING DIAMETER (in / mm) POWER VQLTAGE / Phase (50 hz or 60 hz) Full Load Current / Breaker (amps) - 1PH CONNECTIONS Water Inlet (GHT / BSP) Steam Inlet (BSP)	22.05 / 560 208-240 / 3PH 7.5 / 25 1" / 1" 3/4"	208-240 / 3PH 11 / 40 1" / 1" 3/4"	27.56 / 700 208-240 / 3PH 15 / 50 1.5" / 1.5" 11/4"
DOOR OPENING DIAMETER (in / mm) POWER VOLTACE / Phase (50 hz or 60 hz) Full Load Ourrent / Breaker (amps) - 1PH CONNECTIONS Water Inlet (GHT / BSP) Steam Inlet (BSP) Drain (in/mm)	22.05 / 560 208-240 / 3PH 7.5 / 25 1" / 1" 3/4"	208-240 / 3PH 11 / 40 1" / 1" 3/4"	27.56 / 700 208-240 / 3PH 15 / 50 1.5" / 1.5" 11/4"
DOOR OPENINGDIAMETER (in / mm) POWER VOLTACE / Phase (50 hz or 60 hz) Full Load Ourrent / Breaker (amps) - 1PH CONNECTIONS Water Inlet (GHT / BSP) Steam Inlet (BSP) Drain (in/mm) OYLINDER SFEED	22.05 / 560 208-240 / 3PH 7.5 / 25 1" / 1" 3/4" 3 / 76	208-240 / 3PH 11 / 40 1" / 1" 3/4" 3 / 76	27.56 / 700 208-240 / 3PH 15 / 50 1.5" / 1.5" 11/4" 4 / 102
DOOR OPENINGDIAMETER (in / mm) POWER VOLTACE / Phase (50 hz or 60 hz) Full Load Ourrent / Breaker (amps) - 1PH CONNECTIONS Water Inlet (GHT / BSP) Steam Inlet (BSP) Drain (in/mm) CYLINDER SFEED Washing Speed (rpm)	22.05 / 560 208-240 / 3PH 7.5 / 25 1" / 1" 3/4" 3 / 76 42.5	208-240 / 3PH 11 / 40 1" / 1" 3/4" 3 / 76 38	27.56 / 700 208-240 / 3PH 15 / 50 1.5" / 1.5" 11/4" 4 / 102 34
DOOR OPENINGDIAMETER (in / mm) POWER VOLTAŒ / Phase (50 hz or 60 hz) Full Load Ourrent / Breaker (amps) - 1PH CONNECTIONS Water Inlet (GHT / BSP) Steam Inlet (BSP) Drain (in/mm) CMUNDERSFEED Washing Speed (rpm) Spinning Speed (rpm)	22.05 / 560 208-240 / 3PH 7.5 / 25 1" / 1" 3/4" 3 / 76 42.5 934	208-240 / 3PH 11 / 40 1" / 1" 3/4" 3 / 76 38 875	27.56 / 700 208-240 / 3PH 15 / 50 1.5" / 1.5" 11/4" 4 / 102 34 678
DOOR OPENING DIAMETER (in / mm) POWER VOLTAŒ / Phase (50 hz or 60 hz) Full Load Ourrent / Breaker (amps) - 1PH CONNECTIONS Water Inlet (GHT / BSP) Steam Inlet (BSP) Drain (in/mm) CYLINDER SPEED Washing Speed (rpm) Spinning Speed (rpm) GForce	22.05 / 560 208-240 / 3PH 7.5 / 25 1" / 1" 3/4" 3 / 76 42.5 934	208-240 / 3PH 11 / 40 1" / 1" 3/4" 3 / 76 38 875	27.56 / 700 208-240 / 3PH 15 / 50 1.5" / 1.5" 11/4" 4 / 102 34 678

What makes Fagor a true commercial product and energy efficient?

Standard Features: Heavy duty frame Stainless steel panels Hinged control panel Flexible water level setting 5 compartment supply dispenser 8 external liquid supply dispenser Water reuse capable Enclosed heavy duty drive motor Large door opening Third inlet valve Wet cleaning capable Traceability – storage of data.

## **Optional Features:**

I

Double drain kit allow the recovery of the water, with important savings.

Drain-pump kit (25lbs and 30lbs).

Double heating electric-steam kit.

6 extra signals for automatic liquid dosing.

Industrial voltage:  $440 \div 480$  III without neutral - 50 / 60 Hz.

To learn more, or to find a distributor in your area, visit www.fagorcommercial.com



\* Agency approvals may vary depending on configuration. Consult factory or dealer for details. For the most accurate information, please consult machine installation manual for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change.

